


NUTS

SPRING NUTS Flat Type

TINNERMAN® NUT ALTERNATIVES

Fasteners By Design Inc.



STEEL SPRING NUTS FLAT TYPE						Tinnerman®, SAE J891	
Industry Part Number	Screw Size	L	W	T	PERFORMANCE DATA		
		Length	Width	Material Thickness	Recommended Installation Torque (lb.-in.)	Ultimate Tensile Strength (lb.)	
					Max	Min	
C105SS-440-4	4-40	.44	.25	.012	3	100	
C430-1032-4	10-32	.75	.44	.017	-	-	
C7000-4-4	4A or B	.38	.25	.022	9	300	
C7000-632-4	6-32	.44	.28	.017	6	155	
C7000-6-4	6A or B	.50	.31	.025	12	500	
C7000-832-4	8-32	.50	.31	.017	8	200	
C7000-8-4	8A or B	.63	.41	.028	20	620	
C1150-1024	10-24	.73	.44	.022	14	315	
C7000-1024-4	10-24	.63	.38	.022	14	315	
C7000-10-4	10A or B	.75	.50	.031	35	1000	
C7000-1420	1/4-20	.75	.50	.025	35	570	

Description	A one piece, self-locking fastener made of spring steel. The perimeter of the nut is rectangular in shape. Some variations have an arched base and/or corners which are trimmed or turned.
Applications/ Advantages	It reduces inventories by eliminating need for lockwashers and spanners. Its single thread engagement design makes it easy to apply and remove. Parts are reusable. Provides the correct amount of spring tension without damaging enamel, glass or porcelain surfaces.
Material	SAE 1050 or higher carbon steel, with the exception of part# C105SS-440-4 which is made of stainless steel.
Hardness (Steel)	For material thickness 0.017-0.024 in., Rockwell 30N C40 minimum, C50 maximum. For material thickness 0.025-0.039 in., Rockwell 45N C40 minimum, C50 maximum.
Plating	See Appendix-A for information on the plating of steel spring nuts.

Tinnerman® is a registered trademark of Trans Technology Engineered Components, LLC, Eaton Yale & Towne Inc.. Kanebridge's spring nuts are not manufactured by or connected with the producers of Tinnerman® nuts.